



## Fire Break II percolating Hose

Available in 1" and 1.5"

- Premium single-jacket fire hose, fully synthetic, durable, and lightweight. Its patented Hydra-Wick® self-wetting process produces an effect that keeps the outer jacket moist.
- Its Mertex® lining provides low friction for maximum flow and superior adhesion.
- Resistant to chemical products, petroleum derivatives, ozone, UV rays, hydrolysis, decomposition, and mold. Remains flexible down to -55°C (-65°F).
- Can be used with quick-connect and threaded couplings.
- Meets all performance requirements of NFPA 1961, ULC S519.1, and Underwriter's Laboratories & Factory Mutual.

### TECHNICAL SPECIFICATIONS – 1" DIAMETER:

LENGTH	30 mts.
BURST PRESSURE	900 PSI
WORKING PRESSURE	300 PSI

### TECHNICAL SPECIFICATIONS – 1.5" DIAMETER:

LENGTH	30 mts
BURST PRESSURE	1000 PSI
WORKING PRESSURE	300 PSI

**INFOREST SRL:** [www.inforest.com.ar](http://www.inforest.com.ar)  
[ventas@inforest.com.ar](mailto:ventas@inforest.com.ar) | [comex@inforest.com.ar](mailto:comex@inforest.com.ar)  
**INFOREST IBÉRICA:** [www.inforestiberica.com](http://www.inforestiberica.com)  
[info@inforestiberica.com](mailto:info@inforestiberica.com)



QR: Use your camera or bar code scanner and download the digital PDF version