

Dual-Purpose Ground Monitors



Style 620 Dual-Purpose Ground Monitor

Style 620 monitor shown with
Style 120 quad stacked tips



Dual-Purpose Ground Monitors



Style 620 Dual-Purpose Ground Monitor

- Suitable for use as a portable monitor or a deck gun with features to meet the changing demands of the fire service
- Full 3" water way for flow rate up to 800 GPM (3030 LPM)
- Full 360° rotation in the deck model, 180° in the portable models
- Vertical travel of 63° from 12° to 75° above with inbuilt 37° safety stop from 18° to 55° above
- Compact folding base can be stored in any truck compartment or pre-connected in the hose bed
- Carbide-tipped spikes for extended resistance to wear
- Large handle for excellent portability
- Fully enclosed worm gear is protected from the elements
- Dual integrated ball shut off enables shut off at both monitor inlet for enhanced control and flexibility
- Compatible with a wide range of Protek nozzles and accessories

Style 620				
Max. GPM (LPM)	800 (3030)		Finish	Red Powder Coating
Inlet	Size	2-1/2" (x2)	Friction Loss	15 psi at 800 gpm
	Type	Thread		12 psi at 750 gpm
Outlet	2-1/2"		Travel	63° Vertical
Control	Single Hand-Wheel			180° Rotation
Material	Alloy		Weight Lbs (kg)	37 (16.8 kg)



Style 656
The pipe



Style 656 shown with
Style 620 monitor liftoff



Style 120
Quad Stacked Tips



Style 190
Direct Mount Flange



Style 119
Stream Shaper



Style 847
Monitor Nozzle



Style 887
Self-Ducting Nozzle
(500 GPM)



Style 888
Self-Ducting Nozzle
(750 GPM)

