



## ForestGuard II Dry Hose

Available in 1" and 1.5"

### USES:

Hose for forestry use, fully synthetic, non-self-wetting, approved by ULC.

### DESIGN AND MATERIALS

Single-jacket, synthetic fire hose resistant to chemical products, petroleum derivatives, ozone, UV rays, hydrolysis, decomposition, and mold.

Remains flexible down to -55°C (-65°F).

Lightweight, durable, and versatile, with Mertex® lining that reduces friction loss.

Available with Permatak HPTM treatment for abrasion, moisture, and mold resistance.

Can be used with quick-connect and threaded couplings.

### CERTIFICATIONS

Meets all performance requirements of NFPA 1960 (1961), Canadian Standard ULC S518.1.11, Factory Mutual, and USDA Specification 5100-187C Type 1 for 1" (25 mm) and 1½" (38 mm) hoses.



QR: Use your camera or bar code scanner and download the digital PDF version

### TECHNICAL SPECIFICATIONS 1" DIAMETER:

LENGTH	30 mts
BURST PRESSURE	1000 PSI
WORKING PRESSURE	300 PSI

### TECHNICAL SPECIFICATIONS 1.5" DIAMETER:

LENGTH	30 mts.
BURST PRESSURE	1000 PSI
WORKING PRESSURE	300 PSI

HOSE SPEC.	TRADE SIZE		BOWL SIZE		WEIGHT UN-COUPLED <sup>100'</sup> (30.5M)		COIL DIAMETER 100' (30.5M)		SERVICE PRESSURE		PROOF PRESSURE		BURST PRESSURE	
	In.	mm.	In.	mm.	Lbs	Kg.	In.	Cm.	PSI	kPa	PSI	kPa	PSI	kPa
704	1	2,5	1 5/32	29	8	3,6	14	35,6	300	2070	600	4140	1000	6900
705	1,5	38	1 11/16	43	11,8	5,4	14	35,6	300	2070	600	4140	1000	6900