



TECHNICAL SPECIFICATIONS

- Mitsubishi MEIKI engine, 2.4 HP, 47 cc, 2-stroke.
- Operates efficiently on any slope.
- Centrifugal clutch.
- Easy starting with decompression system.
- Impact guard to protect the underside of the fuel tank.
- Auxiliary remote fuel connection system (RFT).
- Auxiliary fuel supply options available for Chrysler, Mercury, or SAE-style fuel connectors.
- Optional electronic shut-off switch for overspeed protection.
- Electronic ignition.
- The pump delivers minimum flow and pressure values as shown in the performance chart.
- Optional: portable backpack unit.

OPTIONAL

Part No.	Description
A	02PIFRMH0033 Inforest rigid backpack.
B	70FLPFT5 25 L / 6.6 U.S. gallon fuel tank.
C	70FLPFL-M Complete fuel line for Mercury tank.
D	71W11-RFTKIT-M Wick 100G remote fuel connection kit / Mercury.
E1	70FLHPPQC Hydro-Wick® manual primer – 38 mm / 1½" quick coupling QC.
E2	70FLHPPPS Hydro-Wick® manual primer – 38 mm / 1½" female NPSH.
E2	70FLHPPNH Hydro-Wick® manual primer – 38 mm / 1½" female NH NST.
F	70FL15TPPS 1½" NPSH thread protector.
F2	6124NM24PF 1½" MNST male to 1½" NPSH female extruded adapter.
F3	6324QC27 1½" female NPSH to QC adapter.
G	70FL15DLPS10 Reinforced low-pressure suction hose Draftlite 1½"/38 mm x 10' / 3 m NPSH.
H	70FLFV15PF Foot valve with aluminum filter 1½"/38 mm female NPSH.

WICK® 100M

Part No.	Description
71WICK100M	Wick® 100M Fire Pump – Standard model.
71WICK100M-RFT	Wick® 100M Fire Pump (with Mercury remote tank connection kit).
71WICK100M-RFTCO	Wick® 100M Fire Pump (with Mercury remote tank connection kit and electronic shut-off valve).