



Tipsa Armtex One Hose



QR: Use your camera or bar code scanner and download the digital PDF version

USES:

Developed and recommended for firefighting or industrial applications.

DESIGN AND MATERIALS

- Made with 100% high-tenacity synthetic yarn, circularly woven.
- Nitrile and PVC synthetic rubber, extruded through the weave to create a homogeneous structure.
- Service temperature range: From -30°C (-22°F) to 80°C (176°F).
- Thermal resistance: 600°C (1,112°F) for a minimum of 2 minutes.
- Maximum static resistance: 100 psi (700 kPa).

CERTIFICATIONS:

Certified according to UNE 23091-2A; Australian Standard AS 2792-1992: Fire hose – Delivery layflat or Global Mark according to British Standard BS 6391/Type 3, depending on the model.

Reference	UL Certified Hose Reference	Nominal Internal Diameter		Thickness		Service Pressure		Test Pressure		Burst Pressure		Nominal Weight	
		mm	In.	mm	In.	bar	psi	bar	psi	bar	psi	kg/m	lb/ft
F550012A		25	1	1,9	0,075	40	580	80	1.160	120	1.740	0,21	0,14
F550034A	F550037A*	38	1 ½	2	0,079	21	300	42	600	63	900	0,32	0,22
F550056A		45	1 ¾	2	0,079	21	300	42	600	63	900	0,37	0,25
F550067A		52	2	2,2	0,087	18	250	35	500	52	750	0,47	0,32
F552870A		64	2 ½	2,2	0,087	18	255	35	510	53	765	0,59	0,40
F552142A	F552141A*	65	2 ½	2,2	0,087	18	255	35	510	53	765	0,59	0,40
F550103A		70	2 ¾	2,3	0,091	18	250	35	500	52	750	0,66	0,44
F550114A		75	3	2,3	0,091	15	225	30	450	46	675	0,69	0,46
F550147A		102	4	2,6	0,102	12	170	23	340	35	500	0,95	0,64
F550158A		110	4 ¼	2,6	0,102	10	150	20	300	30	450	1,05	0,71