



## FireBoss® Hose

### USES

Wildland fire hose, resistant and lightweight.

### DESIGN & MATERIALS

- Single-jacket construction, fully synthetic and abrasion-resistant.
- PermatekTMhp treatment against corrosion, moisture absorption, and mildew.
- Mertex® lining, producing extremely low friction loss for maximum flow and superior adhesion for long service life.
- Resistant to most chemicals, petroleum derivatives, ozone, UV exposure, hydrolysis, decomposition, and mildew.
- QC couplings.

### CERTIFICATIONS

- Meets or exceeds all performance requirements of NFPA 1961, Underwriter's Laboratories & Factory Mutual.
- Meets or exceeds all performance requirements of U.S.D.A. Specification 5100-187C Type II.

Specification	Hose Diameter		Coupling Size		Weight 100' (30.5 m) Without Coupling		Coil Diameter 100' (30.5 m)		Service/Working Pressure		Test Pressure		Burst Pressure	
	Pulg.	mm.	Pulg.	mm.	Libras	kg.	Pulg.	cm.	PSI	kPa	PSI	kPa	PSI	kPa
750	1.00	25	15/32	29	9.0	4.1	17.0	43.2	300	2070	600	4140	1000	6900
751	1.50	38	111/16	43	13.5	6.1	17.0	43.2	300	2070	600	4140	1000	6900

### TECHNICAL FEATURES – 1" DIAMETER

Length: 30 m  
Burst pressure: 1000 PSI  
Working pressure: 300 PSI

### TECHNICAL FEATURES – 1.5" DIAMETER

Length: 30 m  
Burst pressure: 1000 PSI  
Working pressure: 300 PSI



QR: Use your camera or bar code scanner and download the digital PDF version