



## Tritón Inflatable Tanks

On-site rapid inflation using an electric pump, creating a highly rigid structure that replaces traditional aluminum frames.

### USES

Designed for the temporary storage of water during wildfire suppression operations and other activities that require on-site supply.

### DESIGN & MATERIALS:

All models include a repair kit with integrated Velcro.

Handles and rings are designed for quick handling and secure fastening.

Can be transported on wildland fire trucks, optimizing space compared to traditional foldable tanks with aluminum structures.






Double wall (Drop-Stitch) made of PVC 2.6kg/m<sup>2</sup> Grey Color. These walls are 20 cm thickness when inflated, to give higher resistance.

Single wall in floor and closures made of PVC 0.9mm - 1.1kg/m<sup>2</sup> Red Color.




25,000 L and 50,000 L models: designed for use with Bambi buckets.

Reinforced top on Tritón 25,000 L and 50,000 L models, preventing damage during use with Bambi buckets.

## MODEL TABLE

Model	Capacity	Dimensions and weight	Materials and Construction	Components
<b>Tritón 2300</b> 	2.300 L /600 gal	38kg Ø 1,8 m × 1,5 m high	0,9 mm PVC + 20 cm drop-stitch (gray and red)	<ul style="list-style-type: none"> <li>- 1 Outlet 3"</li> <li>- 2 Valves</li> <li>- 4 rings and 4 handles</li> <li>- 2 rings for hold hose</li> <li>- Velcro fastener for repair kit</li> </ul>
<b>Tritón 8000</b> 	8.000 L /2.100 gal	52kg Ø 4,0 m × 0,8 m high	0,9 mm PVC + 20 cm drop-stitch (gray and red)	<ul style="list-style-type: none"> <li>- 1 Outlet 3"</li> <li>- 2 Valves</li> <li>- 6 rings and 6 handles</li> <li>- 2 rings for hold hose</li> <li>- Velcro fastener for repair kit</li> </ul>
<b>Tritón 15000</b> 	15.000 L /4.000 gal	85kg Ø 4,0 m × 1,5 m high	0,9 mm PVC + 20 cm drop-stitch (gray and red)	<ul style="list-style-type: none"> <li>- 1 Outlet 3"</li> <li>- 3 Valves</li> <li>- 6 rings and 6 handles</li> <li>- 2 rings for hold hose</li> <li>- Velcro fastener for repair kit</li> </ul>
<b>Tritón 25000</b> 	25.000 L /6.500 gal	175kg Ø 4,5 m × 2,0 m high (with superior reinforcement)	0,9 mm PVC + 20 cm drop-stitch (gray and red)	<ul style="list-style-type: none"> <li>- 1 Outlet 3"</li> <li>- 3 Valves</li> <li>- 6 rings and 6 handles</li> <li>- 2 rings for hold hose</li> <li>- Velcro fastener for repair kit</li> </ul>
<b>Tritón 50000</b> 	50.000 L /13.000 gal	Ø 6,0 m × 2,0 m high (with superior reinforcement)	0,9 mm PVC + 20 cm drop-stitch (gray and red)	<ul style="list-style-type: none"> <li>- 1 Outlet 3"</li> <li>- 3 Valves</li> <li>- 6 rings and 6 handles</li> <li>- 2 rings for hold hose</li> <li>- Velcro fastener for repair kit</li> </ul>

## AVAILABLE ACCESSORIES AND COMPLEMENTS

Accessory	Technical Description
<b>Carry Bag</b> 	Made of PVC with Carrying Strap / available for Tritón 2.300 / 8.000 / 15.000.
<b>0.45 mm PVC floor</b> 	Available for models 2,300 (2,5 × 2,5 m) / 8,000 (4,7 × 4,7 m) / 15,000 (4,7 × 4,7 m) / 25,000 (5,5 × 5,5 m) / 50,000 (6,9 × 6,9 m).
<b>Foldable plastic pallet</b> 	Made of plastic and steel / available for Tritón 25.000 / 50.000. Dimensions: 120 × 100 × 100 cm. Weight: 45 kg. Includes top cover.
<b>Anchoring kit Repair kit</b>	
<b>Inflation system</b>	
<b>150W Cordless Electric Air Pump</b>	12V 10A electric air pump with a 4000 mAh lithium battery. Inflation pressure: 0–20 psi. Dimensions: 24 × 18 × 8.6 cm. Weight: 1.5 kg.
<b>Cordless Air Pump</b>	Optional